


SMD POWER INDUCTORS **CD31** SERIES

外型及尺寸 Shape and size (unit: mm)



产品型号	A±0.3	B±0.3	C±0.3	D	N	J	l	最小包装数数量
CD31	3.0	3.5	1.6	1.0	4.0	1.5	0.8	3/4000PCS/卷

电气参数 Electrical parameters

产品型号	电感量 (uH)	公差 (%)	测试频率	直流电阻 RDC (Ω) (Max)	额定电流 IDC (A) (Max)
CD31-1R5M	1.5	±20	100KHz/0.25V	0.10	1.65
CD31-2R2M	2.2	±20	100KHz/0.25V	0.07	1.57
CD31-3R3M	3.3	±20	100KHz/0.25V	0.12	1.44
CD31-3R9M	3.9	±20	100KHz/0.25V	0.14	1.34
CD31-4R7M	4.7	±20	100KHz/0.25V	0.15	1.32
CD31-5R6M	5.6	±20	100KHz/0.25V	0.18	1.19
CD31-6R8M	6.8	±20	100KHz/0.25V	0.21	1.06
CD31-8R2M	8.2	±20	100KHz/0.25V	0.23	0.94
CD31-100K	10	±10	100KHz/0.25V	0.30	0.80
CD31-120K	12	±10	100KHz/0.25V	0.37	0.75
CD31-150K	15	±10	100KHz/0.25V	0.46	0.69
CD31-180K	18	±10	100KHz/0.25V	0.51	0.64
CD31-220K	22	±10	100KHz/0.25V	0.65	0.58
CD31-270K	27	±10	100KHz/0.25V	0.77	0.53
CD31-330K	33	±10	100KHz/0.25V	1.02	0.47
CD31-390K	39	±10	100KHz/0.25V	1.12	0.42
CD31-470K	47	±10	100KHz/0.25V	1.50	0.36
CD31-560K	56	±10	100KHz/0.25V	1.67	0.34
CD31-680K	68	±10	100KHz/0.25V	1.91	0.33
CD31-820K	82	±10	100KHz/0.25V	2.64	0.31
CD31-101K	100	±10	100KHz/0.25V	2.74	0.30
CD31-121K	120	±10	100KHz/0.25V	3.28	0.20
CD31-151K	150	±10	100KHz/0.25V	4.77	0.16
CD31-181K	180	±10	100KHz/0.25V	4.86	0.15
CD31-221K	220	±10	100KHz/0.25V	4.91	0.14