



Specifications/规格

TYPE NAME: SDRH6D18				
Part No./品名	Inductance/ 电感值 ( $\mu$ H)	Test Condition/ 测试条件	D.C.R./ 直流阻抗 ( $m\Omega$ )MAX.	Saturation Current/ 饱和电流(A)
SDRH6D18-1R2PC	1.2 $\pm$ 25%	100KHz,1V	23.125	5.50
SDRH6D18-1R8PC	1.8 $\pm$ 25%	100KHz,1V	35.800	4.50
SDRH6D18-2R7PC	2.7 $\pm$ 25%	100KHz,1V	44.375	3.60
SDRH6D18-3R9PC	3.9 $\pm$ 25%	100KHz,1V	62.40	3.00
SDRH6D18-4R7PC	4.7 $\pm$ 25%	100KHz,1V	73.20	2.80
SDRH6D18-6R8PC	6.8 $\pm$ 25%	100KHz,1V	102.50	2.35
SDRH6D18-8R2PC	8.2 $\pm$ 25%	100KHz,1V	122.50	2.10
SDRH6D18-100PC	10 $\pm$ 25%	100KHz,1V	156.25	1.95
SDRH6D18-150PC	15 $\pm$ 25%	100KHz,1V	237.50	1.60
SDRH6D18-220PC	22 $\pm$ 25%	100KHz,1V	275.00	1.35
SDRH6D18-330PC	33 $\pm$ 25%	100KHz,1V	467.50	1.10
SDRH6D18-470PC	47 $\pm$ 25%	100KHz,1V	668.75	0.90
SDRH6D18-560PC	56 $\pm$ 25%	100KHz,1V	756.25	0.85
SDRH6D18-680PC	68 $\pm$ 25%	100KHz,1V	947.50	0.70
SDRH6D18-820PC	82 $\pm$ 25%	100KHz,1V	1073.75	0.65
SDRH6D18-101PC	100 $\pm$ 25%	100KHz,1V	1212.50	0.60
SDRH6D18-121PC	120 $\pm$ 25%	100KHz,1V	1612.50	0.58

※ The saturation current when the inductance decreases to 65% of initial value. (Ta=25℃)